# **IN-LINE DRYER**



#### **Product Description**

Our range of Pipeline Dryers are primarily used for reducing the water vapour content to a safe level in compressed air or process gas pipelines. These dryers are suitable for small diameter pipelines, up to 10mm or 3/8", and working pressures of up to 7 bar.

Dryers are usually filled with either silica gel or molecular sieves desiccant for water vapour removal, but the use of different grades of molecular sieves desiccant can provide selective adsorption of other components.

New range of low-cost pipeline dryers from Stream Peak. Available in three sizes; 500 grams, 1000 grams & 2000 grams. The units offer high flow capacity for low pressure applications.

#### **Industries Served**

· Power & Refinery



### **Key Features**

- · Point of use dry air
- · Low cost
- · Easy installation
- · Available with condition indicator
- · Different filtration levels available
- · Compression fitting interface
- · Low medium pressure ratings



# **Product Applications**

- Air Exhaust Lines
- Vacuum Lines
- · Easy installation
- · Low Pressure Compressed Air Lines
- Marine Vehicles

## **Product Specifications**

| Desiccant Type        | Desiccant Capacity | Maximum Working Pressure |
|-----------------------|--------------------|--------------------------|
| Indicating Silica Gel | 0.06kg-0.3kg       | 20 psi                   |

#### **Related Products**



Silica Gel



**Humidity Indicator Card** 



Vent Breathers



**Breather Desiccators** 

