# **GRANULES PACKAGING MACHINE**



Stream Peak's Granuales Packaging Machine is an automated packaging machine suitable for small granules and free flow powder such as; sugar, rice, tea, potato chips, ground coffee, snack food, and other granular food & non-food products. The machine is equipped with a volumetric cup for Granules, for efficient and effective packing and sealing of goods.

Our machine also comes with optional add-on features for various needs such as;

- · Finished Products Conveyor Hot Stamping Date Coder
- · Gas-Flushing Device
- · Perforation Jaw Feature
- · Additional Bag Forming Tube
- · Strip Packs Device
- · Heavy Bag Holder
- · Deflation Device





#### **Industries Served**

- · Pharmaceutical
- Food
- Retail



VFH6-4S-G320 4 Side Seal VFFS Bagger (PLC)



VFH6-3S-G320 3 Side Seal VFFS Bagger (PLC)



VFH6-G420 Pillow Bag VFFS Bagger (PLC)



## **Key Features**

- · Specially for small granule products
- · Efficient and high quality sealing & filling
- · Fully Automated, hassle free
- · Volumetric Cup Dosing System, precise & effective
- · Reduce Costs & Time

## **Technical Specifications**

Model	VFH-G320	VFH-G420	VFH-3S-G320	VFH-4S-G320
Bag Styles	Pillow Bag		3 Side Seal Bag	4 Side Seal Bag
Bag Width	30 to 135mm (1.18 to 5.31")	80 to 190mm (3.15 to 7.48")	25 to 135mm (0.98 to 5.31")	40 to 135mm (1.57 to 5.31")
Bag Length	30 to 180mm (1.18 to 7")	50 to 280mm (1.97 to 11")	30 to 150mm (1.18 to 5.9")	30 to 150mm (1.18 to 5.9")
Product Characteristics	Granules			
Dosing System Compatible	Volumetric Cup			
Filling Range	1-20ml ; 20-90ml ; 22-220ml ; 200-800ml (only for G420) by Option			
Running Motion	Intermittent			
Working Efficiency	40-80 bags/min	20-60 bags/min	40-80 bags/min	35-80 bags/min
Date Coding Can Be	Hot Stamping Coder			
Options Available	Perforation, Gas Flushing, Hot Stamping Coder, Strip Bags			
Film & Reel	0.04-0.12mm (30-120mic.) Real Max. Dia. 400mm (15.75") Real Core Dia. 75mm (2.95")			
	Max. Reel Width 300mm (11.81")	Max. Reel Width 400mm (15.75")	Max. Reel Width 270mm (10.63")	Max. Reel Width 270mm (10.36")
Power & Voltage	1.35KW, AC220V/50Hz	2KW, AC220V/50Hz	1.2KW, AC220V/50Hz	1.8KW, AC220V/50Hz
Dimensions	650*850*1650mm (25.59*33.46*64.96")	820*1220*2000mm (32.28*48*78.74")	650*850*1650mm (25.59*33.46*64.96")	650*850*1650mm (25.59*33.46*64.96")
Machine Weight	250kg	400kg	250kg	250kg

#### **Related Products**



Doy-Pack Packing Machine



Linear Compact Premade Pouch Machine



Rotary Compact Premade Pouch Machine

